Customer No.: 31561
Docket No.: 10545-US-PA
Application No.: 10/708,664

PRELIMINARY AMENDMENTS

To the Claims:

Claim 1. (currently amended) An under bump metallurgy layer, between a bonding pad of a chip and a bump, for improving adhesion between the bonding pad and the bump, [[consisting of]]comprising:

an adhesion layer, disposed on the bonding pad;

a barrier layer, disposed on the adhesion layer; and

a wetting-barrier layer, disposed on the barrier layer and between the barrier layer and the bump, wherein a material of the bump comprises tin, and wherein a material of the wetting-barrier layer is made of nickel, wherein the wetting-barrier layer has a thickness larger than that of the adhesion layer or that of the barrier layer, and the bump is disposed on the wetting-barrier layer and the wetting-barrier layer only covers an upper surface of the barrier layer.

Claim 2. (original) The under bump metallurgy layer of claim 1, wherein a material of the adhesion layer is selected from the following group consisting of titanium (Ti), titanium-tungsten (Ti-W) alloy, chromium (Cr), titanium nitride (TiN), tantalum nitride (TaN), tantalum (Ta), aluminum (Al) and copper (Cu).

Claim 3. (currently amended) The under bump metallurgy layer of claim 1, wherein a material of the adhesion layer is selected from the following group consisting of

JUL-27-2006 THU 18:30 FAX NO.

0. P. 06/13

Customer No.; 31561 Docket No.: 10545-US-PA

Application No.: 10/708,664

titanium, titanium-tungsten alloy, chromium, titanium nitride, tantalum nitride, tantalum

and aluminum, [[when]]and the bonding pad is made of aluminum.

Claim 4. (currently amended) The under bump metallurgy layer of claim 1,

wherein a material of the adhesion layer is selected from the following group consisting of

titanium, titanium-tungsten alloy, chromium, titanium nitride, tantalum nitride, tantalum

and copper, [[when]]and the bonding pad is made of copper.

Claim 5. (original) The under bump metallurgy layer of claim 1; wherein a

material of the barrier layer comprises nickel-vanadium alloy.

Claim 6. (original) The under bump metallurgy layer of claim 1, wherein the under

bump metallurgy layer further comprises an anti-oxidation layer and the anti-oxidation

layer is disposed between the wetting-barrier layer and the bump.

Claim 7. Cancelled.

Claim 8. (currently amended) A flip chip structure, comprising:

a chip having an active surface, a passivation layer and a plurality of bonding pads,

wherein the bonding pads are disposed on the active surface and the passivation layer are

disposed on the active surface exposing the bonding pads;

an under bump metallurgy layer, wherein the under bump metallurgy layer

consisting of comprising:

an adhesion layer, disposed on the bonding pad;

-3-

· JUL-27-2006 THU 18:31 FAX NO. P. 07/13

> Customer No.: 31561 Docket No.: 10545-US-PA

Application No.: 10/708,664

a barrier layer, disposed on the adhesion layer; and

a wetting-barrier layer, disposed on the barrier layer, wherein a material of the

wetting-barrier layer is nickel, and the wetting-barrier layer has a thickness larger than

that of the adhesion layer or that of the barrier layer, and wherein the wetting-barrier layer

only covers an upper surface of the barrier layer; and

a bump, disposed on the wetting barrier layer.

Claim 9. (original) The flip chip structure of claim 8, wherein a material of the

adhesion layer is selected from the following group consisting of titanium (Ti),

titanium-tungsten (Ti-W) alloy, chromium (Cr), titanium nitride (TiN), tantalum nitride

(TaN), tantalum (Ta), aluminum (Al) and copper (Cu).

Claim 10. (currently amended) The flip chip structure of claim 8, wherein a

material of the adhesion layer is selected from the following group consisting of titanium,

titanium-tungsten alloy, chromium, titanium nitride, tantalum nitride, tantalum and

aluminum, [[when]] and the bonding pad is made of aluminum.

Claim 11. (currently amended) The flip chip structure of claim 8, wherein a

material of the adhesion layer is selected from the following group consisting of titanium,

titanium-tungsten alloy, chromium, titanium nitride, tantalum nitride, tantalum and

copper, [[when]] and the bonding pad is made of copper.

Claim 12. (original) The flip chip structure of claim 8, wherein a material of the

-4-

PAGE 7/13 * RCVD AT 7/27/2006 6:28:07 AM [Eastern Daylight Time] * SVR:USPTO-EFXRF-5/19 * DNIS:2738300 * CSID: * DURATION (mm-ss):03-20

Customer No.: 31561
Docket No.: 10545-US-PA
Application No.: 10/708,664

barrier layer comprises nickel-vanadium alloy.

Claim 13. (original) The flip chip structure of claim 8, wherein the under bump metallurgy layer further comprises an anti-oxidation layer and the anti-oxidation layer is disposed between the wetting-barrier layer and the bump.

Claim 14, cancelled.

Claim 15. (original) The flip chip structure of claim 8, wherein a material of the bump is made of tin-silver-copper alloy.

Claim 16. (original) The flip chip structure of claim 8, wherein a material of the bump is made of tin-copper alloy.

Claim 17. (currently amended) The flip chip structure of claim 8, wherein a material of the bump is comprises-tin.

Claims 18-21. Cancelled.